

AMTEC

Applied Manufacturing Technologies, Inc.

TSQ (60, 90, 130, 140 Cups)



Specifications

Model	TSQ 60			TSQ 90			TSQ 130		TSQ 140	
Single Cycle	Yes			Yes			Yes		Yes	
Continuous run	Yes			Yes			Yes		Yes	
Linearly adjustable speed regulation	Yes			Yes			Yes		Yes	
Ink/Doctoring cup diameter	60 mm			90 mm			130 mm		140 mm	
Cycles/hr	20-700			200-700			600-1,500		600-1,500	
Cliché size, max. (mm)	70x350	70x510	70x710	100x440	100x600	100x880	150x730	150x930	150x730	150x930
Print image size, max. (mm)	50x150	50x310	50x510	80x180	80x340	80x540	120x320	120x520	130x320	130x520
Pad stroke onto cliché max.	20-100 mm			20-100 mm			50-95 mm		-	
Control Voltage	24 V/DC			24 V/DC			24 V/DC		24 V/DC	
Printing pressure	2,500 N			2,500 N			6000 N		-	
Drive	Electro-pneumatic			Electro-pneumatic			Electro-pneum.mechanic		Electro-pneum.mechanic	
Control	SPS			SPS			SPS		SPS	
Air consumption/cycle	18 NL			18 NL			6 NL		6 NL	

Website: www.amtecinc.com

Email : sales@amtecinc.com

APPLIED MANUFACTURING TECHNOLOGIES, INC.
 3565 E. Enterprise Drive, Anaheim, CA 92807
 Tel: 714-630-9530 Fax: 714-630-9531 Toll Free: 888-634-1143