

AMTEC

Applied Manufacturing Technologies, Inc.

TTG; TSG (60, 90, 130, 210 Cups)



Specifications

Model	TSG 80/60-90/41		TSG 125/60-150/41				TSG 150/60-130/31		TSG 200/150-210/41	
Single Cycle	Yes		Yes				yes		Yes	
Continuous run	Yes		Yes				yes		Yes	
Double Cycle	Yes		Yes				yes		Yes	
Ink/Doctoring cup diameter	60/90 mm		60/90/130/150 mm				90/130 mm		150/210 mm	
Cycles/hr	400-1,500		200-1,200				400-2,100		200-1000	
Cliché size, max. (mm)	70x140	100x215	70x140	100x215	150x300	160x350	100x215	150x300	160x350	220x500
Print image size, max.	54/80 mm		54/80/120/140 mm				80/120 mm		140/200 mm	
Infinitely variable speed regulation	Yes		Yes				Yes		Yes	
Pad stroke onto component linearly adjustable	20-100 mm		20-100 mm				60-120 mm		150-250 mm	
Printing pressure	1000 N		2,500 N				6000 N		4,500/7,300 N	
Drive	Electro-pneumatic		Electro-pneumatic				Electro-pneum.mechanic		Electro-pneumatic	
Control	PLC		PLC				PLC		PLC	
Air consumption/cycle	4.75 NL		15 NL				0.05 NL		25.5 NL	

Website: www.amtecinc.com

Email : sales@amtecinc.com

APPLIED MANUFACTURING TECHNOLOGIES, INC.
 3565 E. Enterprise Drive, Anaheim, CA 92807
 Tel: 714-630-9530 Fax: 714-630-9531 Toll Free: 888-634-1143